

DATA SHEET

FortiFone™ IP Telephones

FON-175, 380, 480, 570, 575, 675i, C71, D71, D72, H25, and FortiFone Softclient*

Whether you're looking for an entry level or executive style IP phone, stay connected to your calls with a FortiFone IP phone.

Each FortiFone is a feature-rich experience with high quality audio and dedicated keys for the most common features. The FortiFone experience offers a



range of options from phones that can be used in a hotel or waiting room, to phones that offer vivid color screens, with programmable line and extension appearances. Managing calls has never been easier. Stay connected with a complete office phone solution.

Key Features and Benefits

HD Quality Audio What good is a phone if you can't hear your caller?

That's why each of the FortiFones delivers crisp and clear audio through the handset and speaker.

Visual Notifications Always be up to date on calls with easy-to-see missed

call and voicemail notifications.

Key Appearances Programmable key appearances on select models give

you the power to not only monitor lines and extensions, but you can also program the keys for a number of

features available on the FortiVoice.



Combined with the powerful features of the FortiVoice PBX, the FortiFone delivers more than just what you need, it gives you what you want.

- Call forwarding
- Voicemail notification
- One-touch transfers
- Do not disturb
- Conference calling
- Speed dial
- PoE (Power over Ethernet) support
- Auto-discovery for easy setup
- Bluetooth support on select models
- Cordless DECT models



FortiCall VoIP Phone Service www.forticall.com

^{*} Availability of FortiFone models might vary by country, please check with your local Fortinet sales or partners for details.

DESK PHONES

FON-175

Introducing the FON-175, a simple to use IP telephone that works in any office and puts the features you need at your fingertips.

- HD quality audio
- 5 dedicated feature keys
- 2.4 inch color display screen
- Intuitive and user-friendly





FON-380

The FON-380 is a mid-range IP phone designed from the ground up with the user in mind. The crystal clear audio and ease of use with the FortiVoice make this a fantastic phone for use while working from home or in the office.

- 10 dedicated feature keys
- 28 programmable appearance keys
- 3.5 inch color display screens
- Supports both on-premises or cloud solutions
- Configuration is simple and intuitive

FON-480

An enterprise IP phone designed from the ground up to be user-friendly and ready to keep you efficient on all calls.

- Premium audio quality in both handset and speaker
- 10 dedicated feature keys
- 45 programmable appearance keys
- 4.3 inch color display screen
- Built-in Bluetooth headset support
- Supports both on-premises or cloud solutions
- Configuration is simple and intuitive





DESK PHONES



FON-570

Easily control calls at your fingertips with a large, vivid color touchscreen, the FON-570 is a great phone for any office.

- Premium audio quality in both handset and speaker
- 7 inch color touch screen
- 7 dedicated feature keys
- Up to 109 programmable appearance keys

FON-575

The FON-575 was designed for office professionals who need a powerful phone that delivers enhanced call control.

- Crystal clear HD audio on the handset and speakerphone
- 11 dedicated feature keys and
- Up to 106 programmable appearance keys
- 4.3 inch and two 3.5 inch color display screens
- Built-in Bluetooth support for greater connectivity





FON-675i

Introducing the FON-675i, designed for busy executives this phone delivers a great combination of powerful businessclass features and a vivid touchscreen.

- Built-in HD video camera
- 5 dedicated feature keys
- Up to 112 programmable appearance keys
- 7 inch color touch screen
- HDMI out port



CONFERENCE PHONE

FON-C71

The FON-C71 is perfect for small and medium-sized conference rooms, supporting 20-foot and 360-degree voice pick up. This touch-sensitive HD conference phone offers you a great unified communication experience with clear and concise audio.

- Premium HD audio
- Four dedicated feature keys
- Full-duplex technology
- Noise and acoustic echo cancellation on the threemicrophone array
- 3.1 inch 248×120 pixel graphic display
- Connect your mobile phone or PC via Bluetooth





DECT PHONES



FON-D71-H

The FON-D71-H is a high-quality DECT handset delivering cordless convenience with the following key features:

- Compatible with FON-D71-B and FON-D72 base solutions
- 2.4 inch color and easy-to-read screen
- 30 hours of talk time on a single charge
- Full-duplex speaker phone
- Intuitive call handling and message indicators
- Supports nine world languages



FON-D71-B

The FON-D71-B is a single-base DECT solution, optimized for businesses with a smaller footprint office environment. The main features include:

- Requires at least one FON-D71-B base and FON-D71-H handset
- Single-base station supports up to eight handsets
- Able to handle up to eight concurrent calls
- Indoor range up to 50 meters
- Outdoor range up to 300 meters



FON-D72-M and FON-D72-B

The FON-D72-M and FON-D72-B work together as a multi-cell DECT solution that benefits a business with a large footprint and multi-floor offices. This solution features:

- Requires at least one FON-D72-M, FON-D72-B, and FON-D71-H
- Base station manager FON-D72-M supports up to 30 bases
- Supports up to eight handsets per base station, up to a maximum of 100 handsets per FON-D72 solution
- Able to handle up to 100 concurrent calls (requires multiple bases)
- Indoor range up to 50 meters per base station
- Outdoor range up to 300 meters per base station
- Seamless handover and roaming between bases



SOLUTION DEPLOYMENT




FON-D71

The FON-D71 solution benefits offices with a smaller area. It is specifically designed as a single-base solution to manage the registration and calls for up to eight handsets with the FortiVoice.

To get started, you only need one base and one handset:

- FON-D71-B
- FON-D71-H



FON-D72-B

The FON-D72 solution benefits offices with a large area, such as a warehouse and multi-floor buildings that require seamless roaming between bases. This solution consists of a FON-D72-M manager, at least one FON-D72-B base, and one FON-D71-H handset. The FON-D72-M acts as a proxy, managing registrations and call distribution between the bases and handsets with the FortiVoice.

Each FON-D72-B can handle up to eight handsets. Additional bases introduced increase the amount of supported handsets, up to a maximum of 100. Up to 30 additional bases can be added which optimizes multi-cell roaming, giving this solution the ability to service handsets over a much larger range than a single-base solution.

To get started, you only need one manager, one base, and one handset:

- FON-D72-M
- FON-D72-B
- FON-D71-H



HOTEL PHONE



FON-H25

The FON-H25 is a customizable IP phone that feels right at home in a hotel room, waiting room, or in the office.

- High quality audio
- Six dedicated feature keys
- Six programmable keys to configure one-touch access for important calls
- Easily configured



SOFTCLIENT



FortiFone Softclient for Mobile

The FortiFone Softclient for mobile enhances your connection to the office, so you never miss an important call. Transform your mobile device into an extension connected to the FortiVoice phone system, giving you a truly unified communication experience as if you were actually in the office.

- Android and iOS support
- Answer, conference, hold, and transfer calls
- Call other extensions on the FortiVoice
- Visual voicemail
- Hands-free speaker phone option
- Message waiting and missed call notifications
- Five soft keys
- Four dedicated feature keys
- Supports headset use
- User-friendly intuitive interface



FortiFone Softclient for Desktop

The FortiFone Softclient for desktop keeps you moving efficiently throughout your day. As an app on your desktop computer you will be able to make and receive calls with ease, all controlled through a simple and intuitive interface.

- Windows and Mac support
- Answer, conference, hold, and transfer calls
- Call other extensions on the FortiVoice
- Visual voicemail
- Message waiting and missed call notifications
- Five soft keys
- Quick access to History, Contact, and Voicemail
- Supports headset use
- User-friendly intuitive interface



SPECIFICATIONS Desktop FON-175 FON-380 FON-480 FON-570 FON-575 FON-675I **Telephone Features** 2.4" (320×240) 3.5" (480×320) 4.3" (480×272) 7" (800×480) 4.3" (480×272) + 2× 3.5" 7" (800×480) Display color display color display color display color touch screen (320×480) color display color touch screen Programmable phone keys 28 45 29, expandable to 109 106 112 (Line/ Extension/ Queue) Soft keys 4 4 4 Dedicated feature keys 5 10 10 11 Speakerphone Full duplex Full duplex Full duples Full duple Full duple Full duple: **Backlit display** \odot \bigcirc \bigcirc \odot \bigcirc \bigcirc \odot \odot \odot \odot Adjustable phone angle \odot Headset support RJ22 RJ22 RJ22/Bluetooth RJ22 RJ22/Bluetooth RJ22 $\langle \rangle$ \odot \odot \odot \odot \odot Dedicated headset button \odot \odot \odot \odot Call waiting \odot \odot \odot \odot \odot \odot \odot Message waiting indicator \odot Visual voicemail \odot \odot Group paging over speaker \bigcirc \odot $\langle \rangle$ \odot $\langle \rangle$ \odot \odot \odot \odot \odot \odot Intercom over speaker \odot \bigcirc \odot \odot \odot \odot \odot Multiple ring tones 1000 Phone book entries 500 Central Central 1000 2000 Missed call log 100 total 100 total 100 total 100 each 300 total 1500 total Received call log Outgoing call log External IP extension support \odot \bigcirc \odot \odot \odot \bigcirc \bigcirc \odot $\langle \vee \rangle$ \odot $\langle \rangle$ \odot Missed call indicator $\langle \vee \rangle$ \odot \odot \odot \odot \odot Onscreen key labels One-touch Feature Keys \odot Call recording \odot \bigcirc \odot \odot $\langle \rangle$ $\langle \rangle$ $\langle \rangle$ $\langle \rangle$ $\langle \rangle$ Cancel transfer Conference \odot \odot \odot \odot \odot \bigcirc \odot \odot \odot Do not disturb \odot \odot \odot \odot \odot \odot \odot Hold \odot \odot $\langle \rangle$ \odot \odot \odot Intercom paging \odot \odot \odot \odot One-touch blind transfer \bigcirc \odot \odot \odot \odot \odot \odot Redial \odot \odot \odot \odot \bigcirc Speed dial $\langle \vee \rangle$ \odot \odot \odot \odot \odot Trade calls Transfer \odot \odot \odot \odot \odot \odot \bigcirc \odot \odot \odot \odot \bigcirc Voicemail **Network Features** \odot \odot \odot \odot \odot \odot Power over Ethernet (802.3af) **Ethernet ports** 2×10/100 2× 10/100/1000 2× 10/100/1000 2× 10/100/1000 2×10/100/1000 2×10/100/1000 Auto-discovery of FortiVoice \odot \odot \odot \odot \odot \odot system on LAN \bigcirc $\langle \rangle$ $\langle \vee \rangle$ \odot LDAP $\langle \vee \rangle$ \odot \bigcirc \odot \odot \odot \odot LLDP \odot \odot \odot 802.1q - VLAN \odot \odot \odot \bigcirc QoS L2 802.1p \bigcirc $\langle \vee \rangle$ $\langle \vee \rangle$ \odot $\langle \vee \rangle$ $\langle \vee \rangle$ (\odot \odot \odot \odot \bigcirc QoS L3 DSCP \odot \odot \odot \odot \odot \odot 802.1x - Network access control \bigcirc \odot \odot \odot \odot **DHCP** client \odot SNTP client \bigcirc $\langle \vee \rangle$ $\langle \rangle$ \odot \odot \odot \odot SIP (RFC 3261) \bigcirc \odot SIP over UDP \bigcirc \bigcirc \odot \odot \odot SIP over TCP \odot \odot \odot \odot \odot \odot SIP over TLS \bigcirc \odot \odot \odot \odot \odot RTCP $\langle \vee \rangle$ \odot \odot \odot \odot \odot SRTP \odot \odot



SPECIFICATIONS

	Desktop					
	FON-175	FON-380	FON-480	FON-570	FON-575	FON-675I
Management						
TFTP	\odot			⊘	\odot	\odot
ITTP	\odot	\odot	⊘	⊘	\odot	\odot
TTPS	\odot	\odot	⊘	⊘	⊘	\odot
ption 66	\odot	\odot	⊘	⊘	\odot	\bigcirc
leb management portal	\bigcirc			⊘	\odot	\odot
ackup/Restore	\odot	\odot	\odot	\odot	\odot	\odot
yslog	\odot	\odot	\odot	\odot	\odot	\odot
udio Features						
D voice	\odot	\odot	\odot	\odot	\odot	\bigcirc
5.711u	Ø	Ø	\odot	\odot	\odot	
.711a	 Ø	<u>⊘</u>	 ⊘	Ø	Ø	<u>⊍</u>
5.723.1	 Ø	 Ø	<u>O</u>	 Ø	 ⊘	<u> </u>
.729a	 ⊘	 ⊘		 ⊘	 ⊘	 ⊘
.722	 ⊘	 ⊘	<u></u>		 ⊘	<u>O</u>
	<u>V</u>	<u>\O</u>	<u>©</u>	<u>⊘</u>	<u>U</u>	<u>V</u>
5.726	igotimes	<u> </u>	<u> </u>	igorplus	igotimes	\otimes
pus		\otimes	\vee			\bigcirc
l.263, H.264 video codec upport						igotimes
oice activity detection VAD)	\odot	\odot	\odot	\odot	\odot	\odot
omfort noise generation CNG)	\odot	⊘	⊘	⊘	⊘	\odot
daptive jitter buffer	300 ms	500 ms	500 ms	300 ms	300 ms	300 ms
TMF in-band	\bigcirc	\bigcirc	⊘	⊘	\odot	\odot
TMF out-of-band RFC2833)	⊘	\odot	⊘		⊘	Ø
TMF via SIP info	\odot	\odot	\odot	\otimes	\odot	\odot
peration						
lumidity	10-65%	10-95%	10-95%	10-95%	10-95%	10-65%
emperature	0-40°C	0-45°C	0-45°C	-10-50°C	0-45°C	0-40°C
ower class	1	3	3	3	3	3
ower consumption	2.0 watts	11.2 watts	8.1 watts	7.5 watts	7.9 watts	10.0 watts
isplay Languages						
nglish	\odot	\odot	\odot	\odot	\odot	\odot
rench	 ⊘	 ⊘	Ø	 ⊘	 Ø	⊘
panish	<u>O</u>	<u>⊘</u>	 ⊘		<u>O</u>	<u>⊘</u>
hinese – Simplified	<u>U</u>			 ⊘	<u>U</u>	<u> </u>
chinese - Traditional	<u>⊖</u>			⊙	Ø	\bigcirc
atalan					 ⊘	
zech						
utch	\bigcirc					
	<u> </u>					
uskara					<u>\(\text{\rightarrow}\)</u>	
alego					<u> </u>	
erman	$\underline{\otimes}$			Θ	<u> </u>	
ebrew	\bigcirc				$\overset{\sim}{\smile}$	
alian	\boxtimes			Θ	\bigcirc	
apanese	<u>Ø</u>					
lagyar					⊘	
olish	\bigcirc			\bigcirc		
ortuguese	\odot			⊘		
ussian	\odot			⊘	⊘	
lovenian						



SPECIFICATIONS	-Conference	Hotel—	Softcli	ent
	FON-C71	FON-H25	SOFTCLIENT MOBILE	SOFTCLIENT DESKTOP
Telephone Features				
Display	3.1" (248×120) color display			
Soft keys	4	6	6	5
Dedicated feature keys	4	6	4	4
Speakerphone	Full duplex	Full duplex		\odot
Backlit display				<u>-</u> ⊙
Adjustable phone angle				
Headset support			—————————————————————————————————————	\otimes
Dedicated headset button				
Call waiting	⊘	⊘	\odot	⊘
Message waiting indicator	\odot	⊘	\odot	⊘
Visual Voicemail			\odot	⊘
Group paging over speaker	\odot			
Intercom over speaker	\bigcirc			
Multiple ring tones	\bigcirc			
Phone book entries	1000		Unlimited	
Call logs: Missed, Received, Outgoing	100 each		Unlimited (phone memory dependent)	Central
External IP extension support	(V)			
Missed call indicator	 ⊘		 ⊘	<u>©</u>
Onscreen key labels	 ⊘			
One-touch Feature Keys				
Call recording	\bigcirc			
Cancel transfer	<u> </u>			
Conference	······································		\bigcirc	<i>⊙</i>
Do not disturb	······································		Ø	 ⊘
Group paging				<u>V</u>
Hold	Ø		\odot	Ø
Intercom paging				
One-touch blind transfer				
Park				
Pickup specific extension				
Redial	\odot	\odot		
Speed dial				
Trade calls	⊘		\bigcirc	⊘
Transfer		\bigcirc	⊘	\bigcirc
Voicemail	\odot	\odot	\odot	\odot
Network Features	_	_		
Power over Ethernet (802.3af)	<u></u>	⊘		
Ethernet ports	1× 10/100	2× 10/100		
Built in WiFi	<u> </u>			
Auto-discovery of FortiVoice system on LAN	\odot	\odot		
LDAP				
LLDP	\odot	⊘		
802.1q – VLAN	\odot	\odot		
QoS L2 802.1p	\odot	⊘		
QoS L3 DSCP	⊘	⊘		
802.1x - Network access control	⊘	⊘		
DHCP client	\bigcirc	\bigcirc		
SNTP client	<u> </u>	<u> </u>		
SIP (RFC 3261)	<u> </u>	<u> </u>	<u> </u>	<u> </u>
SIP over UDP	<u> </u>	<u> </u>	\bigcirc	
SIP over TCP	<u> </u>	<u>Ø</u>	<u> </u>	
SIP over TLS	⊘	<u></u>	\bigcirc	
RTCP			<u> </u>	
SRTP	\bigcirc	\bigcirc	\bigcirc	
W\$6				(./)



SPECIFICATIONS

	⊢Conference ₇	Hotel —	Softclient	
	FON-C71	FON-H25	SOFTCLIENT MOBILE	SOFTCLIENT DESKTOP
Management				
TFTP	\odot	0		
		<u> </u>		
HTTP	<u>Ø</u>	<u> </u>		<u> </u>
HTTPS	<u> </u>	<u></u>	<u> </u>	\bigcirc
Option 66	\odot	\odot		\bigcirc
Web management portal	\odot	\odot		
Backup/Restore	⊘			
Syslog		Ø		⊘
Audio Features				
HD voice	<u> </u>	<u> </u>		
G.711u	⊘		<u> </u>	<u></u>
G.711a	\odot	\odot	\odot	\odot
G.723.1		⊘		
G.729a	⊘	\odot	\odot	
G.722	⊘	Ø	Ø	\bigcirc
G.726	 Ø	 ⊘	<u>O</u>	
	<u> </u>	<u> </u>	<u> </u>	
Opus				\bigcirc
H.263, H.264 video codec support				
Voice activity detection (VAD)	<u> </u>	⊘		<u></u>
Comfort noise generation (CNG)	\odot	\bigcirc	\odot	\odot
Adaptive jitter buffer	300 ms	300 ms	200 ms	Dynamic
DTMF in-band	⊘	\odot	\odot	\odot
DTMF out-of-band (RFC2833)	<u> </u>	Ø		
DTMF via SIP info	 ⊘	 Ø	 ②	
		<u> </u>	<u> </u>	<u> </u>
Operation				
Humidity	10–95%	10–65%		
Temperature	-10-40°C	0-40°C		
Power class	0	2		
Power consumption	8.0 watts	2.0 watts		
Display Languages				
English	<u> </u>		$\underline{\otimes}$	igotimes
French	⊘			
Spanish	⊘			
Chinese - Simplified				
Chinese – Traditional				
Catalan				
Czech				
Dutch				
Euskara				
Galego				
German	\bigcirc			
Hebrew				
Italian	<u> </u>			
Japanese				
Magyar				
Polish	⊘			
Portuguese	<u> </u>			
Russian	 ⊘			
	<u> </u>			
Slovenian				
Turkish	\odot			



SPECIFICATIONS

Telephone Features Display 2.4" (240×320) c Softkeys 2 Dedicated feature keys 6 Speakerphone Full dup	color display
Softkeys 2 Dedicated feature keys 6	color display
Dedicated feature keys 6	
Speakerphone Full dup	
	lex
Backlit display •	
Headset support 3.5 mm j	ack
Call waiting •	
Message waiting indicator •	
Intercom over speaker •	
Multiple ring tones •	
Phone book entries 100	
Missed call log entries 100	
Received call log entries 100	
Outgoing call log entries 100	
External IP extension support •	
Missed call indicator •	
One Touch Features	
Trade calls •	
Call Transfer •	
Voicemail •	
Display Languages	
English •	
French •	
Spanish •	
German •	
Italian •	
Polish •	
Portuguese •	
Russian •	
Turkish •	

BASE STATION	FON-D71-B	FON-D72-B +
BASE STATION	FON-D/I-B	FON-D72-B +
Base Features		
Support handset	FON-D71-H	FON-D71-H
Maximum number of supported handsets	8	100
Maximum number of concurrent calls	8	100
Maximum number of supported bases	1	30
Mutli-cell roaming		•
Network Features		
Power over Ethernet (802.3af)		
	1× 10/100	1 > 10/100
Ethernet ports (RJ45)	1× 10/100	1× 10/100
Auto-discovery of FortiVoice system on LAN	•	•
LDAP	•	•
LLDP	•	•
802.1q - VLAN	•	•
QoS L 2 802.1p	•	•
QoS L 3 DSCP	•	•
802.1x - Network access control	•	•
DHCP client	•	•
SNTP client	•	•
SIP (RFC 3261)	•	•
SIP over UDP		
SIP over TCP		
	•	•
SIP over TLS	·	•
SRTP	•	•
Management		
TFTP	•	•
HTTP	•	•
HTTPS	•	•
Option 66 (RFC 2132)	•	•
Web portal management	•	•
Backup/Restore	•	•
Syslog	•	•
Audio Features		
HD Voice	•	•
G.711u	•	•
G.711A	•	•
G.729A	•	•
G.722	•	•
G.726	•	•
Voice activity detection (VAD)	•	•
Comfort noise generation (CNG)	•	•
Adaptive jitter buffer	•	•
DTMF in-band	•	•
DTMF out-of-band (RFC 2833)	•	•
DTMF via SIP info	•	•
Operation		
Humidity	10 to 95%	10 to 95%
Temperature	0 to 40°C	0 to 40°C
Power class	1	1
i Owei Class		I



ORDER INFORMATION

PRODUCT	SKU	DESCRIPTION
Desktop Phones		
FortiFone FON-175	FON-175	Entry level IP phone with 2.4-inch color display, PoE and 10/100 LAN and PC connections.
	FC-10-FF175-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-380	FON-380	Mid range IP Phone with 3.5"color screen, 28 programmable keys, PoE and 10/100/1000 LAN and PC connections.
	FC-10-FF380-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-480	FON-480	High end IP Phone with 4.3" color screen, 45 programmable keys, built-in Bluetooth, PoE and 10/100/1000 LAN and PC connections.
	FC-10-FF480-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-570	FON-570	IP phone with 7-inch color touchscreen, 29 programmable keys, PoE and 10/100/1000 LAN and PC connections.
	FC-10-FF570-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-575	FON-575	High-end IP phone with 4.3-inch and dual 3.5-inch color screens, 96 programmable keys, PoE and 10/100/1000 LAN and PC connections.
	FC-10-FF575-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-675i	FON-675i	Executive video IP phone with 7-inch color touchscreen, 100 programmable keys, PoE and 10/100/1000 LAN and PC connections.
	FC-10-FF675-247-02-DD	24×7 FortiCare Contract.
Conference Phone		
FortiFone FON-C71	FON-C71	IP conference phone for small and medium-sized conference rooms with noise and acoustic echo cancelling, 20-foot and 360-degree voice pickup, call recording, build-in Wi-Fi & Bluetooth and linkage to mobile phones or PCs.
	FC-10-FFC71-247-02-DD	24×7 FortiCare Contract.
DECT Phones		
FortiFone FON-D71 base	FON-D71-B	DECT base station with an indoors range of 50 meters and outdoor range 300 meters and supports up to 8 concurrent calls.
station	FC-10-FF71B-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-D71 handset	FON-D71-H	DECT handset (NA) with a 2.4" color display, full duplex speakerphone, 2 soft keys and up to 30 hours of talk time.
	FC-10-FF71H-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-D71 European base station	FON-D71-B-EU	European DECT base station with an indoors range of 50 meters and outdoor range 300 meters and supports up to 8 concurrent calls.
	FC-10-FF71B-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-D71 European	FON-D71-H-EU	European DECT handset (NA) with a 2.4" color display, full duplex speakerphone, 2 soft keys and up to 30 hours of talk time.
handset	FC-10-FF71H-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-D72 base	FON-D72-B	NA DECT multi cell base station with an indoors range of 50 meters and outdoor range 300 meters, supports up to 8 concurrent calls (Requires FON-D72-M).
	FC-10-FF72B-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-D72 manager	FON-D72-M	NA DECT manager for FON-D72-B base stations, supports up to 30 base stations and 100 handsets.
	FC-10-FF72M-247-02-DD	24×7 FortiCare Contract.
FortiFone FON-D72 European base	FON-D72-B-EU	European DECT multi cell base station with an indoors range of 50 meters and outdoor range 300 meters, supports up to 8 concurrent calls (Requires FON-D72-M-EU).
	FC-10-FF72B-247-02-DD	24×7 FortiCare Contract.
FortiFone-FON-D72 European manager	FON-D72-M-EU	European DECT manager for FON-D72-B base stations, supports up to 30 base stations and 100 handsets.
	FC-10-FF72M-247-02-DD	24×7 FortiCare Contract.
Hotel Phone		
FortiFone FON-H25	FON-H25	Hotel IP phone with 6 programmable keys, POE and 10/100 LAN and PC connections (custom decals sold separately FON-H25-DCL-CUST).
	FON-H25-DCL-CUST	Custom decal for FON-H25 phone - 50 pieces.
	FC-10-FFH25-247-02-DD	24×7 FortiCare Contract.
Softclient		
FortiVoice softclient	FVE-SCLIENT-10	License to add 10 FortiVoice softclients to FortiVoice Enterprise system.
	FVE-SCLIENT-100	License to add 100 FortiVoice softclients to FortiVoice Enterprise system.

NOTE: FortiFone products are subject to regional telecommunications regulations. Visit the FortiVoice Global Availability for Phone Systems and Phones datasheet for the list of countries in which FortiFone telephones are available.

FortiCare Services are tailored to meet our customers' deployment and operational needs, no matter the company size or location. Our experts provide accelerated implementation, reliable support, and proactive care to help our customers achieve business continuity with maximum protection.



www.fortinet.com

Copyright © 2021 Fortinet, Inc., All rights reserved. Fortinet*, FortiGate*, FortiGate*, FortiGate*, and FortiGate*, FortiGate*, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet discisalms all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinets General Course, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinets internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.